

000003457 11/19/01

11/19/01  
09/993467  
J1003 U.S. PTO

FORM PTO-1390 (REV. 9-2001)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER 7413-1006
<b>TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371</b>			U.S. APPLICATION NO. (If known, see 37 CFR 1.5)
INTERNATIONAL APPLICATION NO. PCT/US00/13937	INTERNATIONAL FILING DATE 19 May 2000	PRIORITY DATE CLAIMED 25 May 1999	
TITLE OF INVENTION FRAGMENTED TAGGANT CODING SYSTEM AND METHOD WITH APPLICATION TO AMMUNITION TAGGING			
APPLICANT(S) FOR DO/EO/US RICHARD P. WELLE			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. 4. <input type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input checked="" type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). a. <input type="checkbox"/> is attached hereto. b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> An English lanugage translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).  <b>Items 11 to 20 below concern document(s) or information included:</b> 11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input type="checkbox"/> A <b>FIRST</b> preliminary amendment. 14. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment. 15. <input type="checkbox"/> A substitute specification. 16. <input type="checkbox"/> A change of power of attorney and/or address letter. 17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 20. <input type="checkbox"/> Other items or information:			

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)		INTERNATIONAL APPLICATION NO. PCT/US00/13937		ATTORNEY'S DOCKET NUMBER 7413-1006	
<div>21. <input checked="" type="checkbox"/> The following fees are submitted:</div> <div><b>BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO. .... <b>\$1040.00</b>  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$890.00</b>  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$740.00</b>  International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$710.00</b>  International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$100.00</b>  <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b></div>				<b>CALCULATIONS PTO USE ONLY</b>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	\$	
Total claims	60 - 20 =	40	x <b>\$18.00</b>	\$ 720.00	
Independent claims	27 - 3 =	24	x <b>\$84.00</b>	\$ 2016.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ <b>\$280.00</b>	\$
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$ 3446.00	
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				+	\$ 1723.00
<b>SUBTOTAL =</b>				\$ 1723.00	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
<b>TOTAL NATIONAL FEE =</b>				\$ 1723.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property +				\$	
<b>TOTAL FEES ENCLOSED =</b>				\$ 1723.00	
				Amount to be refunded:	\$
				charged:	\$

a. ☒ A check in the amount of \$ 1723.00 \_ to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \$ \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any  
overpayment to Deposit Account No. 19-2500 . A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card  
information should not be included on this form** Provide credit card information and authorization on PTO-2038.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Jon E. Hokanson  
Small Larkin, LLP  
10940 Wilshire Blvd., 18th Floor  
Los Angeles, CA 90024

SIGNATURE

Jon E. Hokanson  
NAME

30,069  
REGISTRATION NUMBER

UKS

- 1 -

## FRAGMENTED TAGGANT CODING SYSTEM AND METHOD WITH APPLICATION TO AMMUNITION TAGGING

### Technical Field

The present invention relates to the field of identification taggants. More specifically, the present invention relates to the identification tagging of ammunition, such as small arms ammunition.

### Background Art

A number of systems have been proposed for use as identification taggants, with an extensive body of work investigating methods for tagging explosives.

With respect to ammunition, a system has been proposed and tested wherein the addition of rare-earth elements to ammunition enhanced the delectability of gunshot residue by giving it an unambiguous composition due to incorporation of elements which are easily detected by neutron activation (Bryan et al., 1966). This method was only intended to provide a positive indication of the presence of gunshot residue. It was neither capable of encoding a usefully large number of identification codes, nor was any attempt made to encode any identification information in the taggants.

### Disclosure of Invention

It is an object of this invention to provide a system of and a method for coding taggants which will facilitate economic generation of a very large number of unique identifying codes.

- 2 -

The method employs a fragmented coding scheme where a code is comprised of several individual components which are not physically connected to one another.

It is further an object of this invention to provide a system of and a method for coding taggants which will minimize the probability of false code readings in chemically reacting or contaminated systems. The method employs a binary or related coding system wherein the value of each bit of the code is indicated by the presence of one component, and the absence of the other component, of a designated pair of chemicals. The method further employs an authentication code system.

It is further an object of this invention to provide a system of and a method for tagging ammunition which will minimize concerns about taggant effects on safety and reliability of the tagged ammunition. The method employs a taggant embedded in a thin layer between the primer and propellant in an ammunition round. The method further employs additional layers of material isolating the taggant layer from the primer and the propellant.

#### Brief Description Of The Drawings

Other objects and advantages of the invention will become apparent from the foregoing detailed description taken in connection with the accompanying drawings, in which

Figure 1 is a partial cross-sectional view of a primer adapted for use with preferred embodiments of the present invention.

Figure 2 is a partial cross-sectional view of a cartridge case and projectile adapted for use with preferred embodiments of the present invention.

### Best Mode for Carrying Out the Invention

Known taggant systems and methods fall into three categories. These include: (1) survivable distributed systems and methods; (2) semi-survivable distributed systems and methods; and (3) particulate systems and methods.

#### Distributed Systems

Distributed systems encode the taggant information in substances which are distributed through one or more components of the ammunition. These taggants encode information either in the presence or absence of certain chemical substances, or in the relative concentration of certain chemical substances. In distributed systems, the tagging chemicals are directly mixed with other components of the ammunition, and may be exposed to the chemical reactions involved in firing the ammunition. This leads to the further subdivision of the distributed category into the survivable and semi-survivable sub-categories. The survivable systems are those in which the taggant information is encoded in substances which, preferably, will not be altered in any way by chemical reactions. The semi-survivable systems include chemicals which may be affected by the chemical reactions, but for which, preferably, the taggant information has a high probability of surviving the reactions.

Of the known systems, only radioactive tracer and isotope ratio systems can be classed as survivable distributed systems. Both of these systems encode information in the isotopic composition of single elements. The chemical reactions involved in firing ammunition will have no significant effect on isotopic compositions. As long as enough atoms can be recovered to determine the isotopic composition of the relevant elements, the taggant information can be read.

An improved coding scheme has been devised which will provide an indication when tagging chemicals are destroyed. In such a case, the analysis will lead to information which is ambiguous rather than erroneous. The method works by using a binary coding scheme where each bit in the binary code is represented by two chemicals, identified for illustration purposes



as chemical A and chemical B. In a representative system the presence of chemical A would indicate a bit value of 0, while the presence of chemical B would indicate a bit value of 1. In analyzing a sample, four outcomes are possible. (1) The presence of only chemical A would indicate a bit value of 0. (2) The presence of only chemical B would indicate a bit value of 1. (3) The absence of both chemicals would indicate that the tagging chemical, and therefore the taggant information, had been destroyed. (4) The presence of both chemicals would indicate that the system had been contaminated, and that therefore the tagging information had been destroyed.

Thus, under most circumstances, the analysis will either give the correct result, or indicate that the information had been destroyed. An incorrect result is possible only in a case where the correct tagging chemical had been destroyed, and the system had been contaminated with the incorrect tagging chemical.

With only two chemicals, one can tag no more than two separate batches of ammunition. A useful system must be able to provide unique identifying information for far more than two batches, and must be able to encode identifying information corresponding to any type of alphanumeric or other identifier. Most commonly, such an identifier would be a serial number composed of arabic numerals, although other identification systems are possible. The term “serial number” is used hereinafter to encompass all types of symbolic identifiers. By combining multiple pairs of chemicals to build up a binary serial number, an arbitrarily large number of batches can be tagged. For example, to identify one million<sup>3</sup> separate batches would require a binary serial number 20 bits long ( $2^{20} = 1,048,576$ ). Tagging these batches using this system would require 40 distinct chemicals, with each of 20 pairs being used to identify the value of one bit in the serial number. If, in analyzing a sample from one of these batches of ammunition, only 19 of the expected 20 chemicals are found, then one bit of the serial number is lost. However, this still narrows the serial number from one million possibilities to only two.

While the system is simple with a binary coding scheme i.e., using base-2 numbers, there may be benefits to using other bases. For example, triplets of chemicals could be used to encode a base-3 serial number. In this system, the presence of chemical A, B, or C would indicate a value of 0, 1, or 2 for one trit (base-3 digit) in the serial number. The absence of all three of these chemicals would indicate a loss of information, and the presence of two or more of the chemicals would indicate contamination. Using this system, one million batches of ammunition could be tagged with 39 chemicals in 13 triplets ( $3^{13} = 1,594,323$ ). Other bases could also be used, but as the base number gets larger, a point is reached where more rather than fewer tagging chemicals are required. A base-10 system for example, would require 60 chemicals to tag one million batches. The coding system described here could be implemented using ordinary chemical compounds, using compounds in which one or more atoms are substituted with rare isotopes, or using isotopes themselves.

While these improvements will make a semi-survivable distributed system more reliable, survivable systems may be preferable.

One survivable distributed tagging system of the present invention employs only stable isotopes. In this system, unique taggants, each corresponding to a unique identification code, are created by mixing unique combinations of ratios of multiple stable isotopes of one or more elements. The resulting mixture is added to the substance or product to be tagged. When identification is required, the isotope abundance ratios of the taggant element or elements are measured, and the resultant measurements are compared with the appropriate identification tagging records made at the time the substance was tagged.

A code based on an abundance ratio of multiple isotopes of a single element presents two distinct advantages over systems using abundance ratios of elements or compounds. First, the isotopic abundance ratios can be more precisely measured than abundance ratios of



elements or compounds. Second, the isotopic abundance ratio will not be modified by non-nuclear physical or chemical processes except those specifically designed for isotope separation, so the taggant code will not be destroyed by chemical reactions or explosions.

Elements which could be used for this technique include any element with more than one stable isotope. Of the 83 non-radioactive elements known to exist on earth, 62 have more than one stable isotope, and 40 have more than two stable isotopes. The element tin (Sn) has the largest number (10) of stable isotopes for any single element. The following table lists the symbol of each element under the number of stable isotopes for each of the naturally occurring stable elements.

Table I

Elements grouped according to their number of stable isotopes

1	2	3	4	5	6	7	8	9	10
Be	H	O	S	Ti	Ca	Mo	Cd	Xe	Sn
F	He	Ne	Cr	Ni	Se	Ru	Te		
Na	Li	Mg	Fe	Zn	Kr	Ba			
Al	B	Si	Sr	Ge	Pd	Nd			
P	C	Ar	Ce	Zr	Er	Sm			
Sc	N	K	Pb	W	Hf	Gd			
Mn	Cl	U			Pt	Dy			
Co	V					Yb			
As	Cu					Os			
Y	Ga					Hg			
Nb	Br								
Rh	Rb								
I	Ag								
Cs	In								
Pr	Sb								
Tb	La								
Ho	Eu								
Tm	Lu								
Au	Ta								
Bi	Re								
Th	Ir								
	Tl								

Among the 40 elements having more than two stable isotopes, there are a total of 222 stable isotopes. These totals include some isotopes which are slightly radioactive, but which have very long half lives and are present in naturally occurring samples of the elements. In most cases, the relative concentrations of the stable isotopes found in any given element anywhere on earth are constant to within one part in fifty thousand. The ratios are easily and precisely measured by various known techniques. Highly enriched samples of most stable isotopes are available commercially.

In this system, the abundance ratio of two or more isotopes in each of one or more elements in a substance is artificially controlled to provide for subsequent identification of the substance. For example, for labeling, or tagging, ten commercially prepared batches of ammunition, the element europium (Eu) can be used. It has two stable isotopes with atomic masses of 151 and 153. In natural europium, these two isotopes are present in the concentrations 47.77%, and 52.23% respectively. A code can be created for these batches by preparing a series of isotopic samples containing  $^{151}\text{Eu}$  and  $^{153}\text{Eu}$  in a patterned series of ten concentration ratios such as 5/95, 15/85, 25/75, 35/65, 45/55, 55/45, 65/35, 75/25, 85/15, and 95/5, with each ratio assigned to one specific batch. These samples can be prepared either with elemental europium, or with europium as an element in a compound such as  $\text{Eu}_2\text{O}_3$ . A small quantity of one of these samples can be added, by any of a number of means, to each batch of ammunition to be tagged, according to the following table.

Table II

Batch	$^{151}\text{Eu}/^{153}\text{Eu}$ (Abundance Ratio)
0	5/95
1	15/85
2	25/75
3	35/65
4	45/55
5	55/45
6	65/35
7	75/25
8	85/15
9	95/5

Subsequent measurement of the concentration ratio of  $^{151}\text{Eu}$  to  $^{153}\text{Eu}$  in the ammunition, or in the residue left after it is fired, would yield a ratio identifying the batch in which the ammunition was manufactured. In this example, the ten unique values of the concentration ratio can distinguish each of the ten batches of ammunition.

A significant increase in the number of possible unique codes is achieved by using more than one pair of stable isotopes in creating the code. Continuing the above example, the code can be expanded by adding to the ammunition an additional element (e.g. neodymium, Nd) with its own specific concentration ratio of isotopes (e.g.  $^{143}\text{Nd}$  and  $^{146}\text{Nd}$ ). The code can be further expanded by adding a third element with its specific isotope concentration ratio (e.g. dysprosium,  $^{161}\text{Dy}$  and  $^{164}\text{Dy}$ ).

The following table illustrates how a system using these three pairs of isotopes can be used to create an identification code (e.g. a three digit serial number). The first column lists the serial number, the remaining columns list the abundance ratios of each of the europium

isotopes  $^{151}\text{Eu}$  and  $^{153}\text{Eu}$ ; the neodymium isotopes  $^{143}\text{Nd}$  and  $^{146}\text{Nd}$ ; and the dysprosium isotopes  $^{161}\text{Dy}$  and  $^{163}\text{Dy}$ , respectively.

Table III

Serial Number	Isotope Abundance Ratios		
	$^{151}\text{Eu}/^{153}\text{Eu}$	$^{143}\text{Nd}/^{146}\text{Nd}$	$^{161}\text{Dy}/^{163}\text{Dy}$
000	5/95	5/95	5/95
001	5/95	5/95	15/85
002	5/95	5/95	25/75
....	....	....	....
009	5/95	5/95	95/9
010	5/95	15/85	5/95
011	5/95	15/85	15/85
....	....	....	....
099	5/95	95/5	95/5
100	15/85	5/95	5/95
101	15/85	5/95	15/85
....	....	....	....
998	95/5	95/5	85/15
999	95/5	95/5	95/5

By reference to this table, measurement of the three abundance ratios  $^{151}\text{Eu}/^{153}\text{Eu}$ ,  $^{143}\text{Nd}/^{146}\text{Nd}$ , and  $^{161}\text{Dy}/^{163}\text{Dy}$  in a tagged substance will allow determination of the identification code (e.g. the serial number) of the substance. In this table, not all possible entries are shown. Using the coding scheme of Table III, a total of  $10^3$  or 1000 unique serial numbers can be created. Additional pairs of isotopes could be used to provide additional digits, thereby increasing the number of available serial numbers. Following the same pattern, a system using  $N$  pairs of isotopes to create serial numbers results in  $10^N$  unique serial numbers.

The example illustrated in Table III utilized 10% variations in the concentration ratios of each of the isotope pairs. In fact, smaller variations in the isotopic concentration ratios can be used and measured with sufficient accuracy to be useful in the present invention. When two pairs of isotopes are each controlled and measured to within 1% and combined in a single code, there are  $100^2$  or ten thousand (10,000) unique codes available. Three pairs of isotopes at 1% precision would provide for  $100^3$  or one million (1,000,000) unique codes. By extension, N pairs of isotopes, each controlled and measured to within 1% and combined in a single code, would produce  $100^N$  unique codes. This system will allow simple and economic generation of a very large number of unique codes, such as would be useful for ammunition tagging.

#### Particulate Systems

The particulate category comprises those systems where the taggant information is encoded in small particles which are designed to survive the firing of the ammunition. An example in this category is the color coded plastic beads currently used for tagging explosives in Switzerland. Alternative identifying means also have been proposed for coding the particles, including particle shape, chemical composition, or even microscopic writing. Two principal issues arise when considering application of particulate taggants to ammunition. (1) If the particles are substantially destroyed in the firing of the ammunition, the taggant signal will be degraded or lost. For this reason, the particles are intentionally designed to be robust. This may lead to concerns about their potential effects on firearm mechanisms. (2) The particles are typically manufactured at a remote site, and in large batches, with every particle in a given batch having the same code. Under systems proposed to date, generating one million unique taggant codes would require fabricating one million batches of particles. In the current state of the art,

A solution to the second problem is to use a fragmented coding system in which each particle encodes only a portion of a serial number. How this system would reduce the required number of distinct batches of particles is best illustrated by example. Suppose it is desired to have a given factory produce a run comprising a series of one million ammunition batches, each with its own serial number. If each taggant particle encodes an entire serial number, this would require one million unique batches of particles. Using a fragmented coding system, the same one million batches could be tagged with 301 batches of taggant particles as follows. The first batch of particles (called the master batch) would contain identifying information about the factory and the run, and could be encoded using any of a number of identifying means as described above. The remaining 300 batches of particles would consist of particles coded with a three element coding system, such as a three-band color code. These batches of particles would be divided equally into three groups; A, B, and C. The one hundred particle batches in group A would consist of particles where the first band is always one color, say blue. The remaining two bands would use a 10 color code to indicate the value of two digits of a digital serial number. The one hundred particle batches in groups B and C would similarly have a first band identifying the group, say yellow and red respectively. The remaining two bands would encode two digits of a digital serial number in the same manner as group A. Each batch of ammunition could then be uniquely identified by introducing particles from the master batch, and from one batch from each of groups A, B, and C. Assume that the 10-color encoding scheme follows the example of the electronics industry and used black, brown, red, orange, yellow, green, blue, violet, gray, and white to represent the digits 0 through 9 respectively. Then ammunition batch number 576,039, for example, would be tagged with the master particles, and with three additional particle

batches. The first of these would have blue, green, and violet bands, with the green and violet representing 5 and 7 respectively, and the blue indicating that they encode the first two digits of the serial number. The second batch of particles would have yellow, blue, and black bands, and the third would have red, orange, and white bands. If a sample of residue from the ammunition in this batch is found, the taggant code could be read by finding a particle from each of the four particle batches. The numbers used here were picked for example purposes only. A similar method could be used employing six particle groups, each encoding only one digit of a digital serial number. This would require only 61 batches of particles for one million serial numbers. It is also possible to employ non-digital serial numbers. For example, an 8-color code could be used to encode base-8 serial numbers. Likewise, a 12-color code could be used to encode base-12 serial numbers. Identifying means other than color coding could also be used to encode the serial number components on the particles, or to identify which digits of the serial number are being encoded.

The key to reducing the total number of unique batches of particles, and thereby improve manufacturability, is the use of multiple batches of particles to encode a serial number piece by piece. An assembly line would then only need to control the injection of particles from selected batches to build up a large number of serial numbers from a relatively small number of distinct batches of particles. While very useful for ammunition, where identification of large numbers of separate batches would be useful for law enforcement purposes, the method proposed here has more general utility for any field of manufacture where there exists a need to separately identify a large number of discrete units of production. Examples include, but are not limited to, paint, crude oil, fuel oil, hazardous waste, paper, ink, drugs, raw materials used in the manufacture of drugs, chemicals, compact disks, laser disks, computer disks, video tapes, audio tapes, electronic

circuits, explosives, currency, clothing, computers, electronic components, and automotive components.

Particulate tagging systems can also be combined advantageously with isotopic or chemical tagging systems. One disadvantage of the isotope ratio and chemical tagging systems is that it is not obvious whether or not a taggant is present in a given sample. Without resorting to a sophisticated chemical analysis, a tagged sample will appear identical to an untagged sample. A solution to this difficulty is to combine the isotopic taggant system with another system using particulates that are visible with the unaided eye, or with a simple magnifying glass or microscope. The primary purpose of the particulate taggant would be to indicate the presence of the isotopic or chemical taggant. The particulate taggant may also encode some information, such as the identity of the manufacturer, type of ammunition, date of manufacture, or place of manufacture, but because of its greater versatility, the isotopic or chemical taggant would carry most or all of the identifying information.

For any tagging system, there can be a concern about tags which have been counterfeited, altered, or contaminated by other tags. For example, if two rounds of ammunition were produced with powder tagged using the isotope ratio technique, then combining the powder from those two rounds would produce isotope ratios that would match neither of the initial tags. Subsequent reading of the isotope ratio in the powder would not identify either of the initial two batches, but could incorrectly identify a third unrelated batch as the source of the tag.

A way to avoid this problem is to use one or more additional pairs or multiples of isotopes to create an authentication code. Each taggant value would have a corresponding authentication code. If a taggant code is accidentally created by combining two other codes, or through some other contamination process, it is unlikely that the correct authentication code would also be created. The degree of improbability is determined by the number of unique



authentication codes. The following simplified example illustrates the technique. Assume that there are two batches of powder tagged using the isotope ratio system at 10% resolution. The first one is tagged with europium using the isotopes  $^{151}\text{Eu}$  and  $^{153}\text{Eu}$  in the ratio 25/75. This batch also contains an authentication code in the form of neodymium, with the isotopes  $^{143}\text{Nd}$  and  $^{146}\text{Nd}$  in the ratio 45/55. The second batch of powder is also tagged with europium, using the isotopes  $^{151}\text{Eu}$  and  $^{153}\text{Eu}$  in the ratio 45/55. This batch also contains an authentication code in the form of neodymium, with the isotopes  $^{143}\text{Nd}$  and  $^{146}\text{Nd}$  in the ratio 5/95. If these two batches were mixed in equal amounts, the taggant code of the europium in the combined batch would be read as 35/65, and the authentication code of the neodymium would be read as 25/75. As the taggants were using 10% variations in concentration ratios in forming the code, there is only one chance in 10 that this would be the correct authentication code. By using higher precisions, such as 1% resolution in forming the isotope ratio codes, and additional pairs or multiples of isotopes, the probability of accidentally producing a correct authentication code can be made arbitrarily small. Similar authentication coding schemes can be used for particulate and chemical taggants. It may also be advantageous to create an authentication tag using a different system altogether than the identification tag. For example, a fragmented particulate identification taggant could be combined with an isotopic authentication taggant. Other combinations are also possible.

#### Methods of Application

Regardless of what type of taggant is used, the taggant must be applied to the ammunition so as to acceptably balance user concerns about possible effects on safety and performance, and the utility of the taggant. The most useful taggant will be one that can be read from the smallest sample of projectile, projectile fragment, or gunshot residue collected from a crime scene.

Gunshot residue typically consists of two types of particles. The first is recondensed projectile material which was vaporized by frictional heating of the projectile as it passed through the barrel of the firearm. The second type of particle is composed of the solid residue left behind by the reaction of the primer and propellant charges. Typically, the primer produces the majority of this material. Because most recovered projectiles and projectile fragments will be coated with detectable gunshot residue, a taggant which is uniformly dispersed in the gunshot residue will be of maximum utility. Ideally, it should be present at a concentration high enough to be read from a single residue particle.

An obvious way to maximize uniform distribution of the taggant in the residue would be to distribute it uniformly in the propellant charge (typically gunpowder). This method was used in most of the ammunition taggant tests conducted to date. Unfortunately, this method has the drawback that the taggant is in direct contact with the propellant, leading to concerns about sensitizing the propellant for premature ignition.

An alternative would be to blend the taggant with the primer reactants. The firing of the ammunition results in mixing of the primer reaction products with the propellant, thereby igniting the propellant. If the taggant is carried in the primer reaction products, it will be blended with the propellant as it is ignited, and will then be distributed throughout the gunshot residue. This method has the advantage that the taggant is not exposed to the propellant before the propellant is ignited. The concern about sensitizing the propellant is removed. However, in this method, the concern is transferred to the primer, which may be even more sensitive to the taggant than is the powder.

In an ideal case, the taggant would not be mixed with either the primer or propellant prior to firing the ammunition. This may be accomplished by placing the taggant between the primer and the propellant. When the ammunition is fired, the primer chemicals produce hot reaction

To eliminate any remaining concern about possible sensitization of either the primer or the propellant by the taggant, the taggant can be isolated from both by having it sandwiched between two layers of materials known to be compatible with primer and propellant exposure, respectively. These layers would be of a predetermined thickness sufficient to ensure that the taggant remains isolated from both the primer and the propellant until the ammunition is fired. The isolating layers can be made of any material which is easily shredded, vaporized, burned, or otherwise destroyed by the expanding vapor plume of primer reaction products. Examples of possible barrier materials include paper, wax, and certain plastics. Other materials useful for this application are considered to be equivalents. Figure 1 is a diagram of a primer showing how this system could be applied. The primer cup **10** contains the primer reactants **12**, over which is deposited a protective layer **14**, a taggant layer **16**, and an additional protective layer **18**.

The following is a specific embodiment of this system. In manufacturing a round of .38 caliber handgun ammunition, a primer is fabricated using a brass cup containing approximately 15 mg of primer chemicals. Over this is deposited a thin layer of wax, an additional layer containing approximately 15 ng of europium with the isotopes  $^{151}\text{Eu}$  and  $^{153}\text{Eu}$  in the ratio 25/75, and a final thin layer of wax. The primer is inserted into an empty brass case, to which is added approximately 200 mg of gunpowder propellant, and a projectile. When the round of ammunition has been fully assembled as described, neither the primer nor the propellant is exposed to the europium taggant.

When this round of ammunition is fired, the hot expanding vapors from the reaction of the primer chemicals will shred and vaporize the wax layers. The europium will be entrained in the primer vapor and will mix with the propellant as it is ignited. The europium will be oxidized, forming europium oxide, which will condense and mix with the gunshot residue. Since the europium was present initially at one part per million of the primer mass, any residue particle formed of primer material will contain at least 1 ppm of europium. Since the chemical reactions involved will not significantly alter the isotopic abundance ratio, the europium in the gunshot residue particles will have the same isotopic composition as the original taggant. A typical residue particle might have a mass of  $3 \times 10^{-10}$  g, and will contain at least  $3 \times 10^{-16}$  g of europium. This is about 1.2 million atoms. Measurement of the isotopic composition of the europium in this particle is possible using various mass spectrometric techniques. The number of atoms present is sufficient to ensure a statistically significant reading of the abundance ratio to better than 1% precision. Reading of this ratio will yield the original tagging isotopic composition, and therefore the serial number of the ammunition batch.

An alternative to the wax encapsulated taggant would be to use a pellet insert. The pellet would be fabricated from a material, such as paper, which is easily destroyed by the chemical reaction of the primer or propellant. For example, a small disk of paper would be wetted with a volatile solvent containing a non-volatile taggant. The solvent would be allowed to evaporate, leaving the taggant in the paper. The dry paper disk would then be inserted into the primer cartridge. This is illustrated in Figure 1, where taggant-containing pellets **20** are shown embedded within the primer reactants. Alternatively, the pellets **22** are attached to the surface of the primer reactants. When the ammunition is fired, the pellet would be destroyed and the taggant would be entrained by the primer vapors, mix with the igniting propellant, and ultimately condense in the gunshot residue. Such paper taggants could also simply be inserted in the

cartridge case along with the propellant. This is illustrated in Figure 2 where the cartridge case 30 contains propellant 32 and a projectile 34. The taggant pellets 36 are distributed throughout the propellant. Alternatively, the taggant pellets 38 can be added after the propellant, and remain between the propellant and the projectile. The paper would be destroyed in firing the ammunition and the taggants would be dispersed.

In the pellet system, the taggant would be dispersed throughout the pellet, which acts as a carrier. Alternatively, the taggant may be completely enclosed in a small capsule made of a material easily destroyed in firing the ammunition. This will further ensure that the taggant is completely isolated from the propellant or primer reactants. The taggant capsules could be deployed in the ammunition in the same manner as the pellets described above.

To reduce the risk of tampering, the taggant may be deposited such that it is covered by the primer reactants. The taggant may be deposited in the primer case prior to loading the primer reactants. This is illustrated in Figure 1, where a taggant layer 24 is covered by a protective layer 26, and further covered by the primer reactants 12. If the taggant is easily vaporized, and is covered by a protective layer which is also easily vaporized, the firing of the ammunition would result in the taggant vapor being mixed with the primer vapor as it is expelled into, and ignites, the propellants. The taggant will thus be incorporated in the gunshot residue as it condenses.

If it is desired to tag the ammunition without tagging the primer, one could deposit the taggant on the inner wall of the cartridge case, and cover it with a layer of material to isolate it from the propellant. When the ammunition is fired, the covering layer and the taggant will be vaporized, entrained in the burning propellant, and ultimately deposited with the gunshot residue.

Were ammunition manufactured on an assembly line, with all the components moving sequentially through the various processing steps into the final packaging for shipment, it would be straight-forward to maintain a clear correspondence between position on the assembly line and

- 20 -

the serial number of the ammunition round. This would be very useful for any system incorporating taggants in the primer, since primers are normally manufactured early in the process.

Current manufacturing processes, however, typically have the primers being fabricated in batches, which are then installed in cartridge cases in such a way that it would be difficult to keep track of the taggant serial number for any given round of ammunition.

A process which would eliminate this issue would be to print a small unique machine-readable label, such as a barcode, on each primer. A record is maintained of the correspondence between the barcode and the taggant code. As each round of ammunition is boxed for final shipment, the barcode of each primer is read, and a record is maintained of each taggant code in any given box of ammunition.

It is understood that the above-described preferred embodiments and examples are simply illustrative of the general principles of the present invention. Other formulations, arrangements, assemblies and materials may be used by those skilled in this art and which embody the principles of the present invention, which is limited only by the scope and spirit of the claims set forth below.

What is claimed is:

1. Tagged ammunition comprising:

a projectile;

a cartridge case;

a propellant;

a primer including primer reactants; and

a taggant contained in the primer.

2. The tagged ammunition of claim 1 wherein the taggant is an ingredient in a mixture that includes the primer reactants.

3. The tagged ammunition of claim 1 wherein the taggant is positioned on the surface of the primer reactants.

4. The tagged ammunition of claim 3 further including a material of predetermined thickness positioned between the primer reactants and the taggant.

5. The tagged ammunition of claim 3 further including a material of predetermined thickness positioned between the propellant and the taggant.

6. The tagged ammunition of claim 4 further including a material of predetermined thickness positioned between the propellant and the taggant.

7. Tagged ammunition comprising:

- a projectile;
- a cartridge case;
- a propellant;
- a primer having a primer case and primer reactants; and
- a taggant on the surface of the primer case.

8. The tagged ammunition of claim 7 further including a material of predetermined thickness positioned between the primer reactants and the taggant.

9. Tagged ammunition comprising:

- a projectile;
- a cartridge case;
- a propellant;
- a primer;
- a capsule made of a material capable of being destroyed during firing of the ammunition;
- and
- a taggant positioned within the capsule.

10. The tagged ammunition of claim 9 wherein the capsule is positioned within the cartridge case.

11. The tagged ammunition of claim 9 wherein the capsule is positioned in the primer.



12. Tagged ammunition comprising:

a projectile;

a cartridge case;

a propellant;

a primer;

a pellet made of a material capable of being destroyed during firing of the ammunition;

and

a taggant positioned within the pellet.

13. The tagged ammunition of claim 12 wherein the pellet is positioned within the cartridge case.

14. The tagged ammunition of claim 12 wherein the pellet is positioned in the primer.

#### Method of Tagging Ammunition

15. A method of tagging ammunition having a projectile, a primer, and a propellant comprising:

selecting a taggant; and

incorporating the taggant within the primer.

16. A method of tagging ammunition having a projectile, a propellant, and a primer including primer reactants comprising:

selecting a taggant; and

mixing the taggant with the primer reactants.

17. A method of tagging ammunition having a projectile, a propellant, and a primer including primer reactants comprising:

selecting a taggant; and

depositing the taggant on the surface of the primer reactants.

18. The method of claim 17 further including:

depositing a layer of material of predetermined thickness between the primer reactants and the taggant.

19. The method of claim 17 further including:

depositing a layer of material of predetermined thickness between the propellant and the taggant.

20. The method of claim 19 further including:

depositing a layer of material of predetermined thickness between the primer reactants and the taggant.

21. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer comprising:

selecting a taggant; and

depositing the taggant in a layer in the cartridge case.

- 25 -

22. The method of claim 21 further including:

depositing a layer of material of predetermined thickness between the cartridge case and the primer reactants.

23. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer including primer case and primer reactants comprising:

selecting a taggant; and

depositing the taggant in a layer in the primer case; and

depositing the primer reactants in the primer case so as to cover the taggant.

24. The method of claim 23 further including:

depositing a layer of material of predetermined thickness between the primer case and the primer reactants.

25. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer comprising:

selecting a taggant; and

depositing the taggant within a capsule made of a material easily destroyed during firing of the ammunition; and

depositing said capsule in the cartridge case.

26. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer comprising:

selecting a taggant; and

- 26 -

depositing the taggant within a capsule made of a material easily destroyed during firing of the ammunition; and

depositing said capsule in the primer.

27. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer comprising:

selecting a taggant; and

depositing the taggant within a pellet made of a material easily destroyed during firing of the ammunition; and

depositing said pellet in the cartridge case.

28. A method of tagging ammunition having a cartridge case, a projectile, a propellant, and a primer comprising:

selecting a taggant; and

depositing the taggant within a pellet made of a material easily destroyed during firing of the ammunition; and

depositing said pellet in the primer.

#### Fragmented Particulate Taggants

29. A particulate taggant for identifying a predetermined, encoded serial number comprising:

a first type of particle encoding a first portion of said serial number comprising:

a first code, representative of said first portion of the encoded serial number; and

a second code, identifying a particle to be one of the first type; and

a second type of particle encoding a second portion of said serial number comprising:

a fourth code, identifying a particle to be one of the second type.

30. The taggant of claim 29 further including:

a third type of particle encoding a third portion of said serial number comprising:

a fifth code, representative of a third portion of the encoded serial number; and

a sixth code, identifying a particle to be one of the third type.

31. The taggant of claim 29 further including:

multiple additional types of particles, each additional type of particle encoding one additional portion of said serial number, and each additional type of particle comprising:

a code, representative of said additional portion of the encoded serial number; and

a code, identifying a particle to be of the type encoding said additional portion of the encoded serial number.

### Methods of Tagging Using Fragmented Particulate Taggants

32. A method of tagging comprising:

selecting a serial number;

selecting a first portion of said serial number;

selecting a second portion of said serial number;

providing a plurality of first type of taggant particles;

each of said first type of taggant particles containing a code indicative of the value of the first portion of said serial number; and

- 28 -

each of said first type of taggant particles containing a code identifying the particle to be one of the first type; and

providing a plurality of second type of taggant particles;

each of said second type of taggant particles containing a code indicative of the value of the second portion of said serial number; and

each of said second type of taggant particles containing a code identifying the particle to be one of the second type.

33. The method of claim 32 further comprising:

providing a plurality of a third type of taggant particles;

each of said third type of taggant particles containing a code indicative of the value of a third portion of said serial number; and

each of said third type of taggant particles containing a code identifying the particle to be one of the third type.

34. The method of claim 32 further comprising:

providing multiple additional types of taggant particles;

each particle of each additional type of particles containing a code indicative of the value of a predesignated additional portion of said serial number; and

each particle of each additional type of particles containing a code identifying the particle to be of the type encoding said predesignated additional portion of the encoded serial number.

Methods of Encoding Distributed Taggants

35. A method of encoding chemical taggants using multiple pairs of chemicals to represent the bits of a binary serial number wherein the presence of one chemical of each pair represents a first predetermined bit value and the presence of the other chemical of each pair represents a second predetermined bit value.
36. The method of claim 35 where one of the predetermined bit values is 0 and the other predetermined bit value is 1.
37. A method of encoding chemical taggants comprising:
- identifying a group of  $M \times N$  distinct chemical taggants where  $M$  and  $N$  are integers; and
  - dividing said chemical taggants into  $M$  groups of  $N$  chemicals each; and
  - assigning one taggant chemical from each of the  $M$  groups to correspond to each integer from 0 to  $N-1$  inclusive; and
  - isolating the substance to be tagged and assigning to it an  $M$ -digit, base- $N$  serial number;
  - and
  - adding to the substance to be tagged a quantity of each of the  $M$  chemicals corresponding to the values of the  $M$  digits in the assigned serial number.
38. The method of claim 37 where at least one of the taggant chemicals is isotopically substituted.
39. A method of encoding isotopic taggants using multiple pairs of isotopes to represent the bits of a binary serial number wherein the presence of one isotope of each pair represents a first

predetermined bit value and the presence of the other isotope of each pair represents a second predetermined bit value.

40. The method of claim 39 where one of the predetermined bit values is 0 and the other predetermined bit value is 1.

41. A method of encoding isotopic taggants comprising:

identifying a group of  $M \times N$  distinct isotopic taggants where  $M$  and  $N$  are integers; and

dividing said isotopic taggants into  $M$  groups of  $N$  isotopes each; and

assigning one taggant isotope from each of the  $M$  groups to correspond to each integer from 0 to  $N-1$  inclusive; and

isolating the substance to be tagged and assigning to it an  $M$ -digit, base- $N$  serial number; and

adding to the substance to be tagged a quantity of each of the  $M$  isotopes corresponding to the values of the  $M$  digits in the assigned serial number.

#### Base- $N$ Taggants

42. A binary taggant comprising:

at least a first chemical pair comprising:

a first chemical of the first chemical pair capable of functioning as a taggant and representative of the first of two binary values; and

a second chemical of the first chemical pair capable of functioning as a taggant and representative of the second of the two binary values.





a first isotope of the second isotope pair capable of functioning as a taggant and representative of the first of two binary values; and

a second isotope of the second isotope pair capable of functioning as a taggant and representative of the second of the two binary values.

47. The binary taggant of claim 45 further comprising:

at least two additional isotope pairs each of said pairs comprising:

a first isotope of each additional isotope pair capable of functioning as a taggant and representative of the first of two binary values; and

a second isotope of each additional isotope pair capable of functioning as a taggant and representative of the second of the two binary values.

48. An encoded taggant system capable of representing any M-digit, base-N serial number where M and N are integers, comprising:

M x N distinct chemicals each capable of functioning as a taggant;

said M x N distinct chemicals grouped into M groups of N distinct chemicals in each of the M groups; and

each of the N distinct chemical in each of the M groups corresponding to one integer from 0 to N-1 inclusive,

whereby a quantity of the distinct chemicals corresponding to the values of a predetermined, M-digit, base-N serial number may be selected and added to a substance assigned to the predetermined serial number.

49. The taggant system of claim 48 wherein at least one of the taggant chemicals is isotopically substituted.

## Methods of Ensuring Authentication For Taggants

50. A method of ensuring the authenticity of an identification taggant comprising:

selecting a first taggant representative of identification information;

selecting a second taggant representative of an authentication code; and

combining the first and second taggants to form an authenticated taggant.

51. The method of claim 50 wherein the first taggant is selected from the group consisting essentially of particulate, chemical, or isotopic taggants and

the second taggant is selected from the group consisting essentially of another one of either particulate, chemical or isotopic taggants.

52. The method of claim 50 wherein the first taggant is a fragmented particulate taggant, and the second taggant is an isotopic taggant.

53. The method of claim 52 where the said identification information is selected from one or more of the identity of the manufacturer, type of ammunition, date of manufacture, and/or place of manufacture.

#### Authenticated Taggants

54. A taggant composition comprising:

- a first taggant encoding identifying information; and
- a second taggant encoding an authentication code.

55. The taggant composition of claim 54 where the first taggant is selected from the group consisting essentially of particulate, chemical, or isotopic taggants, and

the second taggant is selected from the group consisting essentially of another one of either particulate, chemical or isotopic taggants.

56. A taggant composition comprising:

- a particulate taggant; and
- a distributed taggant.

57. The taggant composition of claim 56 wherein the distributed taggant is:

- a distributed chemical taggant.

58. The taggant composition of claim 56 wherein the distributed taggant is:

- a distributed isotopic taggant.

#### Labeled Taggant System and Method

59. A method of tagging ammunition having a projectile, a cartridge, and a primer comprising:

- printing a label on the primer such that it is readable after the ammunition is fully assembled; and

- 35 -

selecting a taggant; and

depositing the taggant in the primer.

60. Tagged ammunition comprising:

a projectile;

a cartridge case;



a primer;

a taggant positioned within the primer; and

a label on the primer visible when the ammunition is fully assembled.

Abstract

The present invention relates to identification tagging, and is specifically directed to identification tagging of ammunition. An isotopic taggant is deposited in a layer at the interface between the primer and the propellant so that, as the ammunition is fired, the taggant is dispersed throughout the propellant. The taggant is thus contained in the gunshot residue formed during the firing, and can be read by analysis of residue particles. Alternatively, the taggant may be deposited in a layer under the primer reactants, or in pellets which are easily destroyed by the chemical reactions involved in firing the ammunition, again dispersing the taggant throughout the propellant and the gunshot residue. Non-isotopic chemical taggants may also be employed if they are encoded so as to minimize the possibility of the information being destroyed or improperly read after the taggants are exposed to the chemical reactions in firing the ammunition. This is accomplished by employing a binary coding system and a system of authentication tags. Particulate taggants may also be used. The required large number of unique identification tags are obtained by using a fragmented coding system wherein each particle encodes only a portion of the serial number.



*Fig. 2*

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)</b>  <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing      OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Attorney Docket Number</b>	7413-1006
	<b>First Named Inventor</b>	Richard P. Welle
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	Not Assigned
	<b>Filing Date</b>	Not Assigned
	<b>Group Art Unit</b>	Not Assigned
	<b>Examiner Name</b>	Not Assigned

**As a below named inventor, I hereby declare that:**

My residence, mailing address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FRAGMENTED TAGGANT CODING SYSTEM AND METHOD WITH APPLICATION TO AMMUNITION TAGGING

(Title of the Invention)

the specification of which

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY)

as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent, inventor's or plant breeder's rights certificate(s), or any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 21 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

## DECLARATION — Utility or Design Patent Application

Direct all correspondence to: <input type="checkbox"/>		Customer Number or Bar Code Label		OR <input checked="" type="checkbox"/>		Correspondence address below	
Name <u>Jon E. Hokanson</u>							
Address <u>Small Larkin, LLP</u> <u>10940 Wilshire Boulevard, 18th Floor</u>							
City <u>Los Angeles</u>				State <u>CA</u>		ZIP <u>90024</u>	
Country <u>US</u>			Telephone <u>310-209-4499</u>			Fax <u>310-209-4450</u>	
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.							
NAME OF SOLE OR FIRST INVENTOR :				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name <u>Richard P</u> (first and middle [if any])				Family Name <u>Welle</u> or Surname			
Inventor's Signature <u>[Signature]</u>						Date <u>11/14/01</u>	
Residence: City <u>Huntington Beach</u>			State <u>CA</u>		Country <u>US</u>		Citizenship <u>US</u>
Mailing Address <u>16351 Grenoble Lane</u> <u>CA</u>							
City <u>Huntington Beach</u>			State <u>CA</u>		ZIP <u>92649</u>		Country <u>US</u>
NAME OF SECOND INVENTOR:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City			State		Country		Citizenship
Mailing Address							
City			State		ZIP		Country
<input type="checkbox"/> Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.							